



- Materials are all sanitary stainless steel SS304
- Product easy to install and operate.
- Adopts arc for transition to ensure no dead angle of sanitary.
- The parts that contact materials are all made of stainless steel SS304
- The stainless steel media filter water tank SS304, which possess stable physical and chemical properties, non-pollution, keeping water quality clean and healthy.
- The product high strength, light weight, beautiful and elegant appearance.
- The product have layer on the surface, which possess superior corrosion resistance, good seal performance.

Model	Vessel Size		THK	Media Qty.	DIA (Da)	Height (LB)	Overall (LA)	Inlet - Outlet	Hand Hold			Suggested Operation	
	inch	cm							mm	liter	mm	mm	mm
MKT-SUS640	6x40	15x100	1.5	15	150	1000	1250	3/4 - 3/4	4	4	-	0.1-0.3	1-2
MKT-SUS848	8x48	20x120	1.5	25	200	1200	1550	1 - 1	4	4	-	0.4-0.6	2-3
MKT-SUS1048	10x48	25x120	1.5	50	250	1200	1550	1 - 1	4	4	-	0.4-1.2	2-3
MKT-SUS1048P	10x48	25x120	1.5	50	250	1200	1550	1 - 1	4	4	4	1.2-1.8	2-3
MKT-SUS1248	12x48	30x120	1.5	75	300	1200	1550	1 - 1	4	4	-	0.8-1.2	2-3
MKT-SUS1248P	12x48	30x120	1.5	75	300	1200	1550	1 - 1	4	4	4	1.2-1.8	2-3
MKT-SUS1448	14x48	35x120	1.5	90	350	1200	1550	1 - 1	4	4	-	0.8-1.5	2-3
MKT-SUS1448P	14x48	35x120	1.5	90	350	1200	1550	1 - 1	4	4	4	1.5-2.0	2-3
MKT-SUS1648	16x48	40x120	1.5	100	400	1200	1700	1 - 1	4	4	-	1.2-2.0	2-3
MKT-SUS1648-2	16x48	40x120	2.0	100	400	1200	1700	1 - 1	4	4	-	1.2-2.0	2-5
MKT-SUS1648P	16x48	40x120	1.5	100	400	1200	1700	1 - 1	4	4	4	2.0-2.3	2-3
MKT-SUS1648P-2	16x48	40x120	2.0	100	400	1200	1700	1 - 1	4	4	4	2.0-2.3	2-5
MKT-SUS1660	16x60	40x150	1.5	120	400	1500	1970	1 - 1	4	4	-	1.2-2.0	2-3
MKT-SUS1660-2	16x60	40x150	2.0	120	400	1500	1970	1 - 1	4	4	-	1.2-2.0	2-5
MKT-SUS1660P	16x60	40x150	1.5	120	400	1500	1970	1 - 1	4	4	4	2.0-3.0	2-3
MKT-SUS1660P-2	16x60	40x150	2.0	120	400	1500	1970	1 - 1	4	4	4	2.0-3.0	2-5
MKT-SUS2048-2	20x48	50x120	2.0	150	500	1200	1700	1.5 - 1.5	6	4	-	3.6-5.4	2-5
MKT-SUS2048P-2	20x48	50x120	2.0	150	500	1200	1700	1.5 - 1.5	6	4	4	4.0-6.2	2-5
MKT-SUS2060-2	20x60	50x150	2.0	200	500	1500	2150	1.5 - 1.5	6	4	-	3.6-5.4	2-5
MKT-SUS2060P-2	20x60	50x150	2.0	200	500	1500	2150	1.5 - 1.5	6	4	4	4.0-6.2	2-5

Model	Vessel Size		THK	Media Qty.	DIA (Da)	Height (LB)	Overall (LA)	Inlet - Outlet	Hand Hold			Suggested Operation	
	inch	cm							mm	liter	mm	mm	mm
MKT-SUS2448-2	24x48	60x120	2.0	250	600	1200	1700	2 - 2	6	4	-	4.8-7.2	2-5
MKT-SUS2448P-2	24x48	60x120	2.0	250	600	1200	1700	2 - 2	6	4	8	6.5-8.5	2-5
MKT-SUS2460-2	24x60	60x150	2.0	300	600	1500	2150	2 - 2	6	4	-	4.8-7.2	2-5
MKT-SUS2460-3	24x60	60x150	3.0	300	600	1500	2150	2 - 2	6	4	-	4.8-7.2	2-7
MKT-SUS2460P-2	24x60	60x150	2.0	300	600	1500	2150	2 - 2	6	4	8	6.5-8.5	2-5
MKT-SUS2460P-3	24x60	60x150	3.0	300	600	1500	2150	2 - 2	6	4	8	6.5-8.5	2-7
MKT-SUS3260-2	32x60	80x150	2.0	525	800	1500	2200	2 - 2	16	8	-	8.0-12.0	2-5
MKT-SUS3260-3	32x60	80x150	3.0	525	800	1500	2200	2 - 2	16	8	-	8.0-12.0	2-7
MKT-SUS3260P-2	32x60	80x150	2.0	525	800	1500	2200	2 - 2	16	8	8	10.0-14.0	2-5
MKT-SUS3260P-3	32x60	80x150	3.0	525	800	1500	2200	2 - 2	16	8	8	10.0-14.0	2-7
MKT-SUS4060-2	40x60	100x150	2.0	825	1000	1500	2500	2 - 2	16	8	-	9.6-14.4	2-5
MKT-SUS4060-3	40x60	100x150	3.0	825	1000	1500	2500	2 - 2	16	8	-	9.6-14.4	2-7
MKT-SUS4060P-2	40x60	100x150	2.0	825	1000	1500	2500	2 - 2	16	8	8	12.5-16.0	2-5
MKT-SUS4060P-3	40x60	100x150	3.0	825	1000	1500	2500	2 - 2	16	8	8	12.5-16.0	2-7
MKT-SUS4860-3	48x60	120x150	3.0	1200	1200	1500	2500	3 - 3	18	16	-	14.0-21.0	2-7
MKT-SUS4860-4.5	48x60	120x150	4.5	1200	1200	1500	2500	3 - 3	18	16	-	14.0-21.0	2-8.5
MKT-SUS4860P-3	48x60	120x150	3.0	1200	1200	1500	2500	3 - 3	18	16	10	20.0-25.0	2-7
MKT-SUS4860P-4.5	48x60	120x150	4.5	1200	1200	1500	2500	3 - 3	18	16	10	20.0-25.0	2-8.5
MKT-SUS6060-4.5	60x60	150x150	4.5	1850	1500	1500	2500	4 - 4	18	16	-	21.0-30.0	2-8.5
MKT-SUS6060P-4.5	60x60	150x150	4.5	1850	1500	1500	2500	4 - 4	18	16	10	28.0-35.0	2-8.5

